

## M5 - M6 POCKET FILTER



### ➤ TECHNICAL SPECIFICATIONS

Filter Media	Synthetic Polyester
Frame Material	Galvanized Sheet Metal
Frame Thickness	20-25 mm
Classification (EN779:2012)	M5 – M6
Classification (ISO 16890)	ePM10
Final Pressure Drop	450 Pa
Max. Temperature	80°C
Max. Humidity	90%
Rated Face Velocity	2,70 m/s



PRODUCT CODE	CLASS EN779:2012	CLASS ISO16890	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	NUMBER OF POCKETS	FILTRATION AREA (m²)	NOMINAL AIR FLOW (m³/h)	INITIAL PRESSURE DROP (± 10 % Pa)	Weight Kg
FB-M5-4C-01	M5	ePM10 55%	287	592	360	4	1,70	1700	90	1,1
FB-M5-6C-01	M5	ePM10 55%	490	592	360	6	2,50	2800	90	1,5
FB-M5-8C-01	M5	ePM10 55%	592	592	360	8	3,40	3400	90	2
FB-M5-4C-02	M5	ePM10 55%	287	592	535	4	2,50	1700	70	1,2
FB-M5-6C-02	M5	ePM10 55%	490	592	535	6	3,80	2800	70	1,8
FB-M5-8C-02	M5	ePM10 55%	592	592	535	8	5,00	3400	70	2,4
FB-M5-4C-03	M5	ePM10 55%	287	592	635	4	3,00	1700	100	1,2
FB-M5-6C-03	M5	ePM10 55%	490	592	635	6	4,50	2800	100	1,9
FB-M5-8C-03	M5	ePM10 55%	592	592	635	8	6,00	3400	100	2,8
FB-M6-4C-01	M6	ePM10 70%	287	592	360	4	1,70	1700	100	1,1
FB-M6-6C-01	M6	ePM10 70%	490	592	360	6	2,50	2800	100	1,5
FB-M6-8C-01	M6	ePM10 70%	592	592	360	8	3,40	3400	100	2
FB-M6-4C-02	M6	ePM10 70%	287	592	535	4	2,50	1700	80	1,2
FB-M6-6C-02	M6	ePM10 70%	490	592	535	6	3,80	2800	80	1,8
FB-M6-8C-02	M6	ePM10 70%	592	592	535	8	5,00	3400	80	2,4
FB-M6-4C-03	M6	ePM10 70%	287	592	635	4	3,00	1700	75	1,2
FB-M6-6C-03	M6	ePM10 70%	490	592	635	6	4,50	2800	75	1,9
FB-M6-8C-03	M6	ePM10 70%	592	592	635	8	6,00	3400	75	2,8