

HEADER TYPE PANEL FILTER



➤ TECHNICAL SPECIFICATIONS

Filter Media	Minipleat Micro Glass Fibre
Frame Material	Plastic
Header Thickness	25 mm for 100 mm Frame 22 mm for 150 mm Frame
Classification (EN779:2012)	M5 – F9
Classification (ISO 16890)	ePM10 – ePM2.5 – ePM10
Gasket	Optional (Polyurethane / Epdm)
Seperator	Hot-melt
Final Pressure Drop	450 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	CLASS EN779:2012	CLASS ISO16890	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)
FCJ-M6-100-01	M6	ePM10 70%	287	592	100	4,5	1700	80
FCJ-M6-100-02	M6	ePM10 70%	490	592	100	7,5	2850	80
FCJ-M6-100-03	M6	ePM10 70%	592	592	100	9	3400	80
FCJ-F7-100-01	F7	Epm1 60%	287	592	100	4,5	1700	120
FCJ-F7-100-02	F7	ePM1 60%	490	592	100	7,5	2850	120
FCJ-F7-100-03	F7	ePM1 60%	592	592	100	9	3400	120
FCJ-F8-100-01	F8	ePM1 70%	287	592	100	4,5	1700	140
FCJ-F8-100-02	F8	ePM1 70%	490	592	100	7,5	2850	140
FCJ-F8-100-03	F8	ePM1 70%	592	592	100	9	3400	140
FCJ-F9-100-01	F9	ePM1 85%	287	592	100	4,5	1700	160
FCJ-F9-100-02	F9	ePM1 85%	490	592	100	7,5	2850	160
FCJ-F9-100-03	F9	ePM1 85%	592	592	100	9	3400	160
FCJ-M6-150-01	M6	ePM10 70%	287	592	150	6,25	1700	110
FCJ-M6-150-02	M6	ePM10 70%	490	592	150	10,4	2850	110
FCJ-M6-150-03	M6	ePM10 70%	592	592	150	12,5	3400	110
FCJ-F7-150-01	F7	Epm1 60%	287	592	150	6,25	1700	135
FCJ-F7-150-02	F7	ePM1 60%	490	592	150	10,4	2850	135
FCJ-F7-150-03	F7	ePM1 60%	592	592	150	12,5	3400	135
FCJ-F8-150-01	F8	ePM1 70%	287	592	150	6,25	1700	160
FCJ-F8-150-02	F8	ePM1 70%	490	592	150	10,4	2850	160
FCJ-F8-150-03	F8	ePM1 70%	592	592	150	12,5	3400	160
FCJ-F9-150-01	F9	ePM1 85%	287	592	150	6,25	1700	180
FCJ-F9-150-02	F9	ePM1 85%	490	592	150	10,4	2850	180
FCJ-F9-150-03	F9	ePM1 85%	592	592	150	12,5	3400	180