

G4 FILTER ROLL



➤ TECHNICAL SPECIFICATIONS

Filter Media	Polyester (PET)
Classification (EN779:2012)	G4
Classification (ISO 16890)	ePMcoarse %60 EU4
Final Pressure Drop	250 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	WIDTH (m)	LENGTH (m)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)	Weight (Kg)
EU4	2	20	40	5400	30	8
EU4	1	20	20	2700	30	4
EU4	0,66	20	13,2	1800	30	2,5

G3 FILTER ROLL

➤ TECHNICAL SPECIFICATIONS



Filter Media	Paint Stop Glass Fibre
Classification (EN779:2012)	G3
Classification (ISO 16890)	ePMcoarse %45 EU3
Final Pressure Drop	250 Pa
Max. Temperature	120 °C
Max. Humidity	100%

PRODUCT CODE	WIDTH (m)	LENGTH (m)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)	Weight (Kg)
EU3	2	20	40	5400	25	9
EU3	1,60	20	32	4320	25	7,2
EU3	1	20	20	2700	25	4,5
EU3	0,75	20	15	2050	25	3,4
EU3	0,70	20	14	1900	25	3,2
EU3	0,65	20	13	1750	25	3