

M5 CEILING FILTER ROLL



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|----------------------|
| Filter Media | Synthetic Fibre |
| Weight | 600 g/m ² |
| Thicjness | 22 mm |
| Classification (EN779:2012) | M5 |
| Flammability (DIN53438) | F1 |
| Final Pressure Drop | 250 Pa |
| Max. Temperature | 90°C |
| Max. Humidity | 100% |



| PRODUCT CODE | WIDTH (m) | LENGTH (m) | FILTRATION AREA (m ²) | NOMINAL AIR FLOW (m ³ /h) | INITIAL PRESSURE DROP (± 10 % Pa) | Weight (Kg) |
|--------------|-----------|------------|-----------------------------------|--------------------------------------|-----------------------------------|-------------|
| M5 | 2 | 20 | 40 | 4000 | 40 | 24 |
| M5 | 1 | 20 | 20 | 2000 | 40 | 12 |

AC IMPEGRATED POLYESTER ROLL

TECHNICAL SPECIFICATIONS



| | |
|--------------------------------|--|
| Filter Media | Activated Carbon Imregnated Polyester |
| Thickness | 12 mm |
| Classification (EN779:2012) | G3 |
| Classification (ISO 16890) | ePMcoarse %45 |
| Flammability (DIN53438) | F1 |
| Final Pressure Drop | 250 Pa |
| Max. Temperature | 90 °C |
| Max. Humidity | 100% |

| PRODUCT CODE | WIDTH (m) | LENGTH (m) | FILTRATION AREA (m ²) | NOMINAL AIR FLOW (m ³ /h) | INITIAL PRESSURE DROP (± 10 % Pa) |
|--------------|-----------|------------|-----------------------------------|--------------------------------------|-----------------------------------|
| AC | 2 | 20 | 40 | 5400 | 40 |