

# HIGH FLOW FILTER - 292



## TECHNICAL SPECIFICATIONS

Filter Media	Minipleat Micro Glass Fibre
Frame Material	Galvanized Steel
Classification (EN1822)	E10-U17
Gasket	Cont. Round PU / Flat Epdm
Seperator	Hot-melt
Sealant	2K Polyurethane
Final Pressure Drop	600 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m <sup>2</sup> )	NOMINAL AIR FLOW (m <sup>3</sup> /h)	INITIAL PRESSURE DROP (± 10 % Pa)
FH-E10-GALV-H-01	E10	305	305	292	5,25	500	210
FH-E10-GALV-H-02	E10	305	610	292	10,5	1000	210
FH-E10-GALV-H-03	E10	610	610	292	21	200	210
FH-H13-GALV-H-01	H13	305	305	292	5,25	500	250
FH-H13-GALV-H-02	H13	305	610	292	10,5	1000	250
FH-H13-GALV-H-03	H13	610	610	292	21	200	250
FH-H14-GALV-H-01	H14	305	305	292	5,25	500	270
FH-H14-GALV-H-02	H14	305	610	292	10,5	1000	270
FH-H14-GALV-H-03	H14	610	610	292	21	200	270
FH-E10-GALV-HM-01	E10	305	305	292	6,75	750	210
FH-E10-GALV-HM-02	E10	305	610	292	13,5	1500	210
FH-E10-GALV-HM-03	E10	610	610	292	27	3000	210
FH-H13-GALV-HM-01	H13	305	305	292	6,75	750	250
FH-H13-GALV-HM-02	H13	305	610	292	13,5	1500	250
FH-H13-GALV-HM-03	H13	610	610	292	27	3000	250
FH-H14-GALV-HM-01	H14	305	305	292	6,75	750	270
FH-H14-GALV-HM-02	H14	305	610	292	13,5	1500	270
FH-H14-GALV-HM-03	H14	610	610	292	27	3000	270

