

V BANK FILTER



TECHNICAL SPECIFICATIONS

Filter Media	Minipleat Micro Glass Fibre
Frame Material	Galvanized Sheet Metal
Classification (EN779:2012)	E10 - U17
Gasket	Optional (Polyurethane/Epdm)
Seperator	Hot-melt
Sealant	2K Polyurethane
Final Pressure Drop	600 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	CLASS EN779:2012	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)
FHW-E10-01	E10	305	305	292	7,5	750	180
FHW-E10-02	E10	305	610	292	15	1500	180
FHW-E10-03	E10	610	610	292	30	3000	180
FHW-H13-01	H13	305	305	292	7,5	750	250
FHW-H13-02	H13	305	610	292	15	1500	250
FHW-H13-03	H13	610	610	292	30	3000	250
FHW-H14-01	H14	305	305	292	7,5	750	280
FHW-H14-02	H14	305	610	292	15	1500	280
FHW-H14-03	H14	610	610	292	30	3000	280
FHW-E10-H-01	E10	305	305	292	10	1000	200
FHW-E10-H-02	E10	305	610	292	20	2000	200
FHW-E10-H-03	E10	610	610	292	40	4000	200
FHW-H13-H-01	H13	305	305	292	10	1000	280
FHW-H13-H-02	H13	305	610	292	20	2000	280
FHW-H13-H-03	H13	610	610	292	40	4000	280
FHW-H14-H-01	H14	305	305	292	10	1000	320
FHW-H14-H-02	H14	305	610	292	20	2000	320
FHW-H14-H-03	H14	610	610	292	40	4000	320