

## MESH PANEL FILTER



### ➤ TECHNICAL SPECIFICATIONS

Filter Media	Expanded Metal Mesh
Frame Material	Galvanized Sheet Metal
Classification (EN779:2012)	G2
Classification (ISO 16890)	ePMcoarse %35
Grid	Metal Mesh
Final Pressure Drop	250 Pa
Max. Temperature	100°C
Max. Humidity	100%
Rated Face Velocity	2,70 m/s



PRODUCT CODE	CLASS EN779:2012	CLASS ISO16890	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA	NOMINAL AIR FLOW (m3/h)	INITIAL PRESSURE DROP (± 10 % Pa)	Weight Kg
FP-G2-01	G2	ePMcoarse 35%	287	287	48	0,35	850	20	0,65
FP-G2-02	G2	ePMcoarse 35%	287	592	48	0,98	1700	20	1,4
FP-G2-03	G2	ePMcoarse 35%	592	592	48	1,20	3400	20	2,65
FP-G2-04	G2	ePMcoarse 35%	287	287	96	0,70	850	25	1,2
FP-G2-05	G2	ePMcoarse 35%	287	592	96	1,96	1700	25	2,55
FP-G2-06	G2	ePMcoarse 35%	592	592	96	2,40	3400	25	3,8

