

AC GRANUL CARTRIDGE FILTER



TECHNICAL SPECIFICATIONS

Filter Media	Pellet Granular Activated Carbon
Frame Material	Electro Galvanized
Classification (EN779:2012)	AC
Final Pressure Drop	70 Pa
Max. Humidity	70%



ACTIVATED CARBON CYLINDRICAL CARTRIDGE FILTER SET

PRODUCT CODE	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	NUMBER OF CARTRIDGE	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)	WEIGHT (kg)
FKT-4-400	305	305	400	4	850	250	12
FKT-8-400	305	610	400	8	1700	250	24
FKT-16-400	610	610	400	16	3400	250	48

ACTIVATED CARBON CYLINDRICAL CARTRIDGE FILTER

PRODUCT CODE	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	NUMBER OF CARTRIDGE	NOMINAL AIR FLOW (m ³ /h)
FKF-KP-400	Ø140	400	215	270	2,5
FKF-İP-400	Ø145	400	215	270	2,5



AC GRANUL PANEL FILTER

TECHNICAL SPECIFICATIONS

Filter Media	Granular Activated Carbon
Frame Material	Galvanized Sheet Metal
Classification (EN779:2012)	AC
Classification (ISO 16890)	ePMcoarse
Gasket	Optional (Polyurethane/Epdm)
Rate Face Velocity	2,50 m/s
Max. Temperature	50°C
Max. Humidity	70%



PRODUCT CODE	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)	Weight (Kg)
FP-ACG-05	287	287	24	150	80	1,2
FP-ACG-06	287	592	24	300	80	2,4
FP-ACG-07	490	590	24	500	80	4
FP-ACG-08	592	592	24	600	80	5
FP-ACG-01	287	287	48	150	140	2,25
FP-ACG-02	287	592	48	300	140	4,5
FP-ACG-03	490	590	48	500	140	7,8
FP-ACG-04	592	592	48	600	140	9,6