


CURLY BRACKET CARTRIDGE



➤ Dimensions Details

| Outer Dimensions (mm) | Inner Dimensions (mm) | Height | Pleat Height (mm) |
|-----------------------|-----------------------|----------|-------------------|
| 328 | 216 | Variable | 48 |

➤ Support Details

| Top/Bottom Caps | Inner Mesh | Gasket |
|-----------------------------|-----------------------------|------------------|
| Galvanized or AISI304 Steel | Galvanized Perforated Sheet | EPDM or Silicone |

➤ Filter Media Details

| Media | Brand | Air Permeability (at 200 Pa) | Pore Size (μ) |
|----------------------------|----------------------|------------------------------|---------------|
| Polyester | General Tekstil (TR) | 85 l/m ² | 5 |
| PTFE Coating Polyester | JP Air (DK) | 370 l/m ² | 1,2 |
| Alu Coating Polyester | JP Air (DK) | 470 l/m ² | 1,2 |
| Oleo/Hydrophobic Polyester | JP Air (DK) | 470 l/m ² | 1 |
| Flame Retardant Blend | Hifyber (TR) | 170 l/m ² | 0,4 |

- Please contact us for custom size filter production.
- Please contact us for filter media suitable for your process.
- We can increase the filter surface areas for the air flow you want

<http://www.filtras.com.tr/>

Tuna Mh. 5601 Sk. No: 4-8 Bornova 35600 İzmir - Türkiye
+90 232 461 1118 - info@filtras.com.tr