

# THREAD FILTER CARTRIDGE



## Outer Dimensions (mm)

279 to 365

## Height (mm)

600  
660  
1000  
1200

## Pleat Height (mm)

15 to 30

## Support Details

Top/Bottom Cap	Inner Mesh	Gasket
Galvanized or AISI304 Steel	Galvanized Perforated Sheet or AISI304 Steel	Needle Felt or Neoprene

## Filter Media Details

Media	Brand	Air Permeability (at 200 Pa)	Pore Size ( $\mu$ )
Polyester	General Tekstil (TR)	85 l/m <sup>2</sup>	5
PTFE Coating Polyester	JP Air (DK)	370 l/m <sup>2</sup>	1,2
Alu Coating Polyester	JP Air (DK)	470 l/m <sup>2</sup>	1,2
Oleo/Hydrophobic Polyester	JP Air (DK)	470 l/m <sup>2</sup>	1

- ➔ Please contact us for custom size filter production.
- ➔ Please contact us for filter media suitable for your process.
- ➔ We can increase the filter surface areas for the air flow you want

<http://www.filtras.com.tr/>

Tuna Mh. 5601 Sk. No: 4-8 Bornova 35600 İzmir - Türkiye  
+90 232 461 1118 - info@filtras.com.tr